760258354 | PPL-FA-3U-HCM



Propel 3RU front access fiber panel for Propel XFrame. Accepts 24, 12 fiber Propel ULL modules, splice cassettes or 6 port adapter packs

- Panel comes with 24 carriers to allow for all front access using standard Propel components. Incoming cable and patch cords are
 routed at the front of the panel
- HCM (Horizontal Cable Management) panels: HCM panels maximize density within the frame. Patch cords are routed across the front of the panel providing maximum frame density
- For use with 12 fiber Propel components

Product Classification

CommScope®		
Fiber patch panel		
Propel		
PPL		

General Specifications

Color	Gray		
Interface, front	Unloaded		
Rack Type	EIA 19 in		
Rack Units	3		
Shelf Movement	Fixed		

Dimensions

Height	134 mm	I	5.276 in
Width	483 mm		19.016 in

Material Specifications

Material Type Aluminum | Steel

Environmental Specifications

Safety Standard UL

Page 1 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 26, 2025



760258354 | PPL-FA-3U-HCM

Packaging and Weights

Packaging quantity

Weight, net 3.583 kg | 7.9 lb

1

Page 2 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 26, 2025

