


# FJ-12S5-HFNN-3M



HELIAX® Discrete, outdoor rated, single mode (G.657.A2) fiber cable assembly, End 1: Duplex SC. End 2: HMFOC (Plug). Main cable length: 0.8 m; Branch cable length: 2.2m, total cable assembly length 3m

## Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Product Type	Wireless Fiber Cable Assemblies
Product Brand	HELIAX®
Product Series	FJ
Ordering Note	ANDREW® non-standard product

## General Specifications


Construction Type	Direct fiber tail
Interface, Connector A	SC Male
Interface Body Style, connector A	Straight
Interface, Connector B	HMFOC
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	12

## Dimensions

Breakout Length, connector A	99.822 mm   3.93 in
Cable Assembly Length	3.048 m   10 ft
Diameter Over Jacket	5.4 mm   0.213 in

## Ordering Tree

# FJ-12S5-HFNN-3M



## Material Specifications

**Jacket Material** Low Smoke Zero Halogen (LSZH)

## Mechanical Specifications

**Minimum Bend Radius, furcation** 61 mm | 2.402 in  
**Minimum Bend Radius, loaded** 108 mm | 4.252 in  
**Minimum Bend Radius, unloaded** 54 mm | 2.126 in

## Optical Specifications

**Fiber Mode** Singlemode  
**Fiber Type** G.657.A2  
**Insertion Loss, typical note** Insertion loss is measured at 1310 and 1550 nm  
**Insertion Loss, typical** 0.3 dB

# FJ-12S5-HFNN-3M

---

**Return Loss, minimum, connector A** 50 dB

## Environmental Specifications

<b>Installation temperature</b>	-10 °C to +70 °C (+14 °F to +158 °F)
<b>Operating Temperature</b>	-40 °C to +75 °C (-40 °F to +167 °F)
<b>Storage Temperature</b>	-40 °C to +75 °C (-40 °F to +167 °F)
<b>Environmental Space</b>	Indoor/Outdoor
<b>Jacket UV Resistance</b>	UV stabilized

## Packaging and Weights

**Cable weight** 29 kg/km | 19.487 lb/kft

## \* Footnotes

**Insertion Loss, typical note** Insertion loss is measured at a room temp of +20°C (+68°F)