F4C-HPHMHR-6M

HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male Right Angle, 6m

Product Classification

Product Type	SureFlex® HP, HELIA	SureFlex® HP, HELIAX® performance	
Product Brand	HELIAX® SureFle	HELIAX® SureFlex®	
Product Series	RSJ4-50		
General Specifications			
Body Style, Connector A	Straight		
Body Style, Connector B	Right angle		
Interface, Connector A	4.3-10 Male		
Interface, Connector B	4.3-10 Male		
Specification Sheet Revision Level	А		
Dimensions			
Length	6 m 19.685 ft		
Nominal Size	1/2 in		
Electrical Specifications			
3rd Order IMD Static Test Method	Two +43 dBm carrier	ſS	
3rd Order IMD, typical	-116 dBm		
DTF, Connector A	-34 dB		
DTF, Connector B	-32 dB		
VSWR/Return Loss			
Frequency Band	VSWR, typical	Return Los	
698–960 MHz	1.083	28	

Frequency Band	VSWR, typical	Return Loss, typical (dB)
698–960 MHz	1.083	28
1700–2200 MHz	1.083	28
2200–2700 MHz	1.135	24
3400–3800 MHz	1.222	20

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4C-HPHMHR-6M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2