## L4A-HPNMNM-1M5

LDF4-50A SureFlex® Jumper with interface types N Male and N Male,

## Product Classification

Product Type	SureFlex® HP, HELIAX® performance	
Product Brand	HELIAX®   SureFlex®	
Product Series	LDF4-50A	
General Specifications		
Body Style, Connector A	Straight	
Body Style, Connector B	Straight	
Interface, Connector A	N Male	
Interface, Connector B	N Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	1.5 m   4.921 ft	
Nominal Size	1/2 in	
Electrical Specifications		
3rd Order IMD Static Test Method	Two +43 dBm carriers	
3rd Order IMD, typical	-112 dBm	
DTF, Connector A	-34 dB	
DTF, Connector B	-34 dB	
VSWR/Return Loss		

Frequency Band	VSWR, typical	Return Loss, typical (dB)
680–960 MHz	1.065	30
1700–2200 MHz	1.065	30
2200–2700 MHz	1.106	26

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

## L4A-HPNMNM-1M5

Jumper Assembly Sample Label



**Environmental Specifications** 

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2