

# FMB12X085-SHG6C1N



Flex Max® FM902 Broadband Bridger Amplifier, 1.2 GHz GaN output, 85-102 MHz Bandpass split, 27 dB Upstream gain, Full station, 40-90 Vac Powering

- \*Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.
- Supports 1.2 GHz Downstream and 204 MHz Upstream bandpass for DOCSIS® 3.1 migration
- Modular RF Electronics package with upgradable frequency split options
- Increased gain to allow drop in upgrades for ≥ 750 MHz spacing
- Mechanically compatible with legacy Flex Net 700/800/900 series and Flex Max 900 and 901 series housings
- Expanded return path bandwidth with support up to 204 MHz
- QAM and analog ADU options for automatic level control and gain hold in the event of pilot loss

## Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Product Type	RF amplifier
Product Series	FM902
Government Requirements	Build America Buy America (BABA) compliant*

## General Specifications

Technology	1.2 GHz GaN output
Housing	Standard (Full station)
Location of Manufacturing	Waived per BABA waiver for BEAD Program

## Dimensions

Width	271.78 mm   10.7 in
Depth	135.89 mm   5.35 in
Length	406.4 mm   16 in

## Electrical Specifications

Upstream Gain	27 dB
Bandpass Split	85/102 MHz

# FMB12X085-SHG6C1N

Input Voltage Range, ac	40–90 V
Level Control	711.00 MHz QAM ALC
Reference Slope	21.1 dB (54-1218 MHz)

## Ordering Tree

F	M	B	1	2	X	0	8	5	—	S	H	G	6	C	1	N
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Key	Technology
FMB12	1.2 GHz GaN Output

Key	Reference Slope
X	21.1 dB (54–1218 MHz)

Key	Bandpass Split
042	42/54 MHz
085	85/102 MHz
204	204/258 MHz

Key	Level Control
X	Manual Level Control (MLC)
A	499.25 MHz ALC
Q	609.00 MHz QAM ALC
S	711.00 MHz QAM ALC

Key	Upstream Gain
H	27 dB

Key	Output Configuration
G	Two bridger outputs—user-configurable to four outputs

Key	Powering
1	None (RF Module Only)
6	2.3A, 90V, 50/60 Hz, High Efficiency

Key	Housing
A	None (RF Module Only)
C	6-port Flex Max, - 20 dB internal test points

Key	Housing Finish
1	Standard

Key	Options
N	N/A

## Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
-----------------------	--------------------------------------

## Packaging and Weights

Weight, net	7.257 kg   16 lb
-------------	------------------

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

