# 860669616-2255



Monopole Hoisting Grip Anchor, for Monopoles 22"-55" OD

Engineered attachment anchor point solution for 22" to 55" diameter monopoles to accommodate and support cable via the wire mesh grip.

-MAXIMUM LOAD PER EYEBOLT = 1000 LBS -MAXIMUM LOAD PER MOUNT = 3000 LBS -REVIEWED FOR USE WITH A MINIMUM POLE DIAMETER OF 10" WITH WALL THICKNESS OF 3/16" AND A YIELD STRENGTH OF 36 KSI. FOR USE ON THINNER MATERIAL REQUIRES ADDITIONAL ENGINEERING REVIEW

Supports all cables types anchored with a hoisting grip including Hybrid cable.

-Competent person to make determination of usage on the structure

#### Product Classification

Product Type	Hoisting Grip Anchor
Warranty	One year

#### General Specifications

Cable Runs, quantity	3
Mounting	Round member
Dimensions	
Height	101.6 mm   4 in

<b>y</b>	
Mounting Diameter, maximum	1,397 mm   55 in
Mounting Diameter, minimum	558.8 mm   22 in

#### Material Specifications

Hot dip galvanized steel

#### Packaging and Weights

Included

Mount | Threaded rod

ANDREW an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 8, 2025

Page 1 of 2

## 860669616-2255

Packaging quantity	1
Weight, net	31.2 kg   68.784 lb
Footnotes	

### Warranty

**y** For more information, please consult our Product Warranty guidelines



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 8, 2025