

# FT-36PAAHIN

HELIAX® Modular Fiber Cable, assembly, 36 multi mode fibers, End 1: DLC GEN1.5; End 2: DLC GEN 1.5; CPR Cca cable. Anti-rodent with E-Glass Protection.

## Product Classification

Regional Availability	Asia   Australia/New Zealand   China   EMEA   Europe   India   Latin America   North America
Product Type	Wireless Fiber Cable Assemblies
Product Series	FT
Ordering Note	ANDREW® non-standard product

## General Specifications

Construction Type	Discrete fiber trunk
Interface, Connector A	LC/UPC
Interface Feature, connector A	Uniboot
Interface Body Style, connector A	Straight
Interface, Connector B	LC/UPC
Interface Feature, connector B	Uniboot
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	36

## Dimensions

Cable Assembly Length Range (m)	1 – 300
Diameter Over Jacket	8.9 mm   0.35 in

## Mechanical Specifications

Minimum Bend Radius	75 mm   2.953 in
Minimum Bend Radius, furcation	10 mm   0.394 in

## Optical Specifications

Fiber Mode	Multimode
Fiber Type	OM4, bend insensitive
Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm
Insertion Loss, typical	0.5

# FT-36PAAHIN

---

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +75 °C (-40 °F to +167 °F)
<b>Environmental Space</b>	Indoor   Outdoor

## Packaging and Weights

<b>Cable weight</b>	300 kg/km   201.591 lb/kft
---------------------	----------------------------

## \* Footnotes

**Insertion Loss, typical note** Insertion loss is measured at a room temp of +20°C (+68°F)