

75 Ohm P3® Trunk and Distribution Cable, black PE jacket with aerial floodant



## Product Classification

<b>Product Type</b>	Coaxial hardline cable
<b>Product Brand</b>	P3®
<b>Warranty</b>	One year

## General Specifications

<b>Cable Type</b>	750 Series
<b>Construction Type</b>	Swaged
<b>Jacket Color</b>	Black

## Dimensions

<b>Cable Length</b>	762 m   2500 ft
<b>Diameter Over Center Conductor, nominal</b>	4.242 mm   0.167 in
<b>Diameter Over Dielectric, nominal</b>	17.323 mm   0.682 in
<b>Diameter Over Jacket, nominal</b>	21.082 mm   0.83 in
<b>Diameter Over Outer Conductor, nominal</b>	19.05 mm   0.75 in
<b>Jacket Thickness, nominal</b>	0.889 mm   0.035 in
<b>Outer Conductor Thickness, nominal</b>	0.864 mm   0.034 in

## Electrical Specifications

<b>Capacitance</b>	50.197 pF/m   15.3 pF/ft
<b>Capacitance Tolerance</b>	±1.0 pF/ft
<b>Characteristic Impedance</b>	75 ohm
<b>Characteristic Impedance Tolerance</b>	±2 ohm
<b>dc Resistance Note</b>	Nominal values based on a standard condition of 20 °C (68 °F)

# 530100203 | P3® 750 JCASP SM MT

<b>dc Resistance, Inner Conductor, nominal</b>	1.87 ohms/km   0.57 ohms/kft
<b>dc Resistance, Loop, nominal</b>	2.493 ohms/km   0.76 ohms/kft
<b>dc Resistance, Outer Conductor, nominal</b>	0.623 ohms/km   0.19 ohms/kft
<b>Jacket Spark Test Voltage</b>	5000 Vac
<b>Nominal Velocity of Propagation (NVP)</b>	87 %
<b>Operating Frequency Band</b>	5–3000 MHz
<b>Structural Return Loss</b>	24 dB @ 1003–1218 MHz   24 dB @ 1219–1794 MHz   30 dB @ 5–1002 MHz
<b>Structural Return Loss, Grade N</b>	≥24 dB @ 1003–1218 MHz   ≥24 dB @ 1219–1794 MHz   ≥30 dB @ 5–1002 MHz

## Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
5.0	0.36	0.11
55.0	1.21	0.37
85.0	1.51	0.46
204.0	2.36	0.72
211.0	2.43	0.74
250.0	2.66	0.81
300.0	2.92	0.89
350.0	3.18	0.97
400.0	3.44	1.05
450.0	3.67	1.12
500.0	3.87	1.18
550.0	4.07	1.24
600.0	4.3	1.31
750.0	4.86	1.48
865.0	5.28	1.61
1002.0	5.72	1.74
1218.0	6.41	1.95
1794.0	8.07	2.46
1800.0	8.08	2.46
2000.0	8.57	2.61
2200.0	9.05	2.76
2500.0	9.73	2.96

# 530100203 | P3® 750 JCASP SM MT

---

<b>2700.0</b>	10.16	3.1
<b>3000.0</b>	10.8	3.29

## Material Specifications

<b>Center Conductor Material</b>	Copper-clad aluminum
<b>Dielectric Material</b>	Foam PE
<b>Jacket Material</b>	PE
<b>Outer Conductor Material</b>	Aluminum

## Mechanical Specifications

<b>Minimum Bend Radius, bonded</b>	152.4 mm   6 in
<b>Pulling Tension, maximum</b>	306.175 kg   675 lb

## Environmental Specifications

<b>Corrosion Protection</b>	Aerial floodant
<b>Environmental Space</b>	Aerial

## Packaging and Weights

<b>Packaging Type</b>	Reel
<b>Weight, gross</b>	398.828 kg/km   268 lb/kft

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system