FD3-MK072J00M0ME0A



Indoor FDH 3000 w/ 72f Shell, 72f distribution loaded, no splitters included, MPO distribution connectors, and a 12f Feeder using Spliced Stranded Loose Tube Pigtails

Indoor FDH 3000 w/ 72f Shell, 72f distribution loaded, no splitters included, MPO distribution connectors, and a 12f Feeder using Spliced Stranded Loose Tube Pigtails

Product Classification

Regional Availability North America

Product Type Fiber distribution hub

Product Series IFDH 3000

General Specifications

Functionality Patching | Splicing

Access Front
Adapters, quantity 72

Cable Type Pigtails - Stranded

Color Putty white

Fibers per Feeder Cable, quantity 12

Front Door Type Single hinged

InterfaceSC/APCMountingWallPort, quantity72Splitter Slots, quantity9

Dimensions

 Height
 533.4 mm | 21 in

 Width
 533.4 mm | 21 in

 Depth
 368.3 mm | 14.5 in

 Cable Length
 30.48 m | 100 ft

Enclosure Size Small

Material Specifications



FD3-MK072J00M0ME0A

Finish Powder coated

Material Type Aluminum

Optical Specifications

Fiber Mode Singlemode

Environmental Specifications

Environmental Space Indoor

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

