# F4A-PNMDF-X

**Base Product** 



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types N Male and 7-16 DIN Female, variable length

### **Product Classification**

**Product Type**Wireless transmission cable assembly

**Product Series** FSJ4-50B

General Specifications

Attachment, Connector B Field attachment

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector AN Male

**Interface, Connector B** 7-16 DIN Female

**Specification Sheet Revision Level** A

**Variable Length** For custom lengths, contact your local ANDREW representative

**Dimensions** 

**Length** 0 m | 0 ft

Nominal Size 1/2 in

Electrical Specifications

**DTF, Connector A** -32 dB

## VSWR/Return Loss

Frequency Band VSWR, typical Return Loss, typical (dB)

**0–3000 MHz** 1.11 26 **2.2–2.7 GHz** 1.09 28

Jumper Assembly Sample Label





# **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

**Agency** 

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

#### Included Products

F4PDF-C

- 7-16 DIN Female connector for 1/2 in FSJ4-50B

cable

