

# L4A-BDFNM

Base Product



LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Female Bulkhead and N Male, variable length

## Product Classification

Product Type	Wireless transmission cable assembly
Product Series	LDF4-50A

## General Specifications

Body Style, Connector A	Bulkhead
Body Style, Connector B	Straight
Interface, Connector A	7-16 DIN Female
Interface, Connector B	N Male
Specification Sheet Revision Level	A
Variable Length	For custom lengths, contact your local ANDREW representative

## Dimensions

Length	0 m   0 ft
Nominal Size	1/2 in

## Electrical Specifications

DTF, Connector A	-32 dB
DTF, Connector B	-32 dB

## Jumper Assembly Sample Label

# L4A-BDFNM



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

## Included Products

LDF4-50A	–	LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)
----------	---	---

# LDF4-50A



LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)

## Product Classification

Product Type	Coaxial wireless cable
Product Brand	HELIAX®
Product Series	LDF4-50A
Ordering Note	ANDREW® standard product (Global)

## General Specifications

Product Number	520094002/00   SZ520094902/00
Flexibility	Standard
Jacket Color	Black
Performance Note	Attenuation values typical, guaranteed within 5%

## Dimensions

Diameter Over Dielectric	12.954 mm   0.51 in
Diameter Over Jacket	15.875 mm   0.625 in
Inner Conductor OD	4.826 mm   0.19 in
Outer Conductor OD	13.97 mm   0.55 in
Nominal Size	1/2 in

## Electrical Specifications

Cable Impedance	50 ohm ±1 ohm
Capacitance	75.8 pF/m   23.104 pF/ft
dc Resistance, Inner Conductor	1.48 ohms/km   0.451 ohms/kft
dc Resistance, Outer Conductor	2.69 ohms/km   0.82 ohms/kft
dc Test Voltage	4000 V
Inductance	0.19 µH/m   0.058 µH/ft
Insulation Resistance	100000 MOhms-km
Jacket Spark Test Voltage (rms)	8000 V

# LDF4-50A

Operating Frequency Band	1 – 8800 MHz
Peak Power	40 kW
Velocity	88 %

## VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
680–800 MHz	1.13	24.3
800–960 MHz	1.13	24.3
1700–2200 MHz	1.13	24.3
2300–2700 MHz	1.13	24.3

## Material Specifications

Dielectric Material	Foam PE
Jacket Material	PE
Inner Conductor Material	Copper-clad aluminum wire
Outer Conductor Material	Corrugated copper

## Mechanical Specifications

Minimum Bend Radius, multiple Bends	127 mm   5 in
Minimum Bend Radius, single Bend	50.8 mm   2 in
Number of Bends, minimum	15
Number of Bends, typical	50
Tensile Strength	113 kg   249.122 lb
Bending Moment	3.8 N-m   33.633 in lb
Flat Plate Crush Strength	2 kg/mm   111.995 lb/in

## Environmental Specifications

Installation temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)
Attenuation, Ambient Temperature	68 °F   20 °C
Average Power, Ambient Temperature	104 °F   40 °C
Average Power, Inner Conductor Temperature	212 °F   100 °C

# LDF4-50A

## Packaging and Weights

**Cable weight** 0.22 kg/m | 0.148 lb/ft

## Regulatory Compliance/Certifications

Agency	Classification
CENELEC	EN 50575 compliant, Declaration of Performance (DoP) available
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

