PTS1P-HMDM-P

Base Product

PTS1-50-P SureFlex® Jumper with interface types 4.3-10 Male and 7-16 DIN Male, Variable Length

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type		Wireless transmission cable assembly
Product Brand		HELIAX® SureFlex®
Product Series		PTS1-50-P
General Specifications		
Body Style, Connector A		Straight
Body Style, Connector B		Straight
Interface, Connector A		4.3-10 Male
Interface, Connector B		7-16 DIN Male
Specification Sheet Revision Level		A
Variable Length		For custom lengths, contact your local ANDREW representative
Dimensions		
Nominal Size		1/4 in
Electrical Specifications		
3rd Order IMD		-110 dBm
3rd Order IMD Test Method		Two +43 dBm carriers
VSWR/Return Loss		
Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.152	23.02
1700–2200 MHz	1.152	23.02

Jumper Assembly Sample Label

2200-2700 MHz

Page 1 of 2



23.02

1.152

PTS1P-HMDM-P



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

-

an Amphenol company

Page 2 of 2

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025