


# UFXLULU62

Base Product



## Ultra Low Loss OM4, LC/UPC Uniboot to LC/UPC Uniboot, 2.0 mm Duplex Fiber Patch Cord, Low Smoke Zero Halogen/Riser

- Patch cords using Uniboot technology combine, modularity, flexibility with easy insertion and removal from connectivity
- Uniboot connectors feature an adjustable polarity via a manual and independent rotation of each single connector body without exposing the fibers
- Uniboot technology features a push-pull mechanism operated by squeezing the connector boot

### Product Classification

|                       |  |
|-----------------------|--|
| Regional Availability | Asia   Australia/New Zealand   Europe   Latin America   Middle East /Africa   North America                              |
| Portfolio             | CommScope®   |
| Product Type          | Fiber patch cord, duplex   |
| Product Brand         | SYSTIMAX ULL   |
| Product Series        | UFX  |
| Ordering Note         | For lengths greater than 999 ft (304 m), orders must be in meters   Minimum length may vary based on cable configuration |

### General Specifications

|                                |         |
|--------------------------------|---------|
| Color, connector A             | Aqua    |
| Color, connector B             | Aqua    |
| Interface, Connector A         | LC/UPC  |
| Interface Feature, connector A | Uniboot |
| Interface, Connector B         | LC/UPC  |
| Interface Feature, connector B | Uniboot |
| Jacket Color                   | Aqua    |
| Total Fibers, quantity         | 2       |

### Dimensions

|                                  |                 |
|----------------------------------|-----------------|
| Cable Assembly Length Range (m)  | 1 – 999         |
| Cable Assembly Length Range (ft) | 1 – 999         |
| Diameter Over Jacket             | 2 mm   0.079 in |

# UFXLULU62

## Ordering Tree



## Mechanical Specifications

**Cable Retention Strength, maximum** 11.24 lb @ 0 ° | 4.40 lb @ 90 °

## Optical Specifications

**Fiber Mode** Multimode  
**Fiber Type** OM4, LazrSPEED® 550 | OM4, bend insensitive  
**Insertion Loss, maximum** 0.15 dB  
**Return Loss, minimum** 35 dB

## Environmental Specifications

**Operating Temperature** -10 °C to +60 °C (+14 °F to +140 °F)  
**Environmental Space** Dual Rated LSZH/Riser

## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| CHINA-ROHS    | Above maximum concentration value  |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS          | Compliant/Exempted   |
| UK-ROHS       | Compliant/Exempted   |



## Included Products

760251107 – Fiber indoor cable, LazrSPEED® Low Smoke Zero Halogen Riser Light Duty Interconnect, 2  
N-002-MP-5K-F20AQ/LTS/D fiber, Multimode OM4, Gel-free, Feet jacket marking, Aqua jacket color

# UFXLULU62

---

860658161 – 2.0 mm LC/UPC Uniboot GEN 1.5, Aqua