# F4A-PDMDR-2M5-X

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle, 2.5 m

### Product Classification

Product Type	SureFlex® standard	
Product Brand	HELIAX®   SureFle	ex®
Product Series	FSJ4-50B	
General Specifications		
Attachment, Connector B	Field attachment	
Body Style, Connector A	Straight	
Body Style, Connector B	Right angle	
Interface, Connector A	7-16 DIN Male	
Interface, Connector B	7-16 DIN Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	2.5 m   8.202 ft	
Nominal Size	1/2 in	
Electrical Specifications		
DTF, Connector A	-32 dB	
VSWR/Return Loss		
Frequency Band	VSWR, typical	Return Loss, typical (dB)
	1 100	

0–3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

### Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

## F4A-PDMDR-2M5-X



#### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

#### Regulatory Compliance/Certifications

#### Agency

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

### Included Products

F4PDR-C – 7-16 DIN Male Right Angle for 1/2 in FSJ4-50B cable

Classification

Page 2 of 2

