F1A-HMNM-5M-P

FSJ1-50A SureFlex® Jumper with interface types 4.3-10 Male and N
Male, 5M

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

1700-2200 MHz

2200-2700 MHz

Product Type		SureFlex® Premium, static PIM	
Product Brand		HELIAX® SureF	lex®
Product Series		FSJ1-50A	
General Specifications			
Attachment, Connector A		Factory attached	
Attachment, Connector B		Factory attached	
Body Style, Connector A		Straight	
Body Style, Connector B		Straight	
Interface, Connector A		4.3-10 Male	
Interface, Connector B		N Male	
Specification Sheet Revision Level		А	
Dimensions			
Length		5 m 16.404 ft	
Nominal Size		1/4 in	
Electrical Specifications			
3rd Order IMD		-107 dBm	
3rd Order IMD Test Method		Two +43 dBm carrie	ers
VSWR/Return Loss			
Frequency Band	VSWR		Return Loss (dB)
698–960 MHz	1.152		23
4700 0000 101	1 1 5 0		00

1.152

1.152

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

23

23

F1A-HMNM-5M-P

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant/Exempted



Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025