# F1A-XMNF-5M-P

FSJ1-50A SureFlex® Jumper with interface types NEX10 Male and N Female, 5 m

### Product Classification

Product Type		SureFlex® Premium, static PIM	
Product Brand		HELIAX®   SureFlex®	
Product Series		FSJ1-50A	
General Specifications			
Body Style, Connector A		Straight	
Body Style, Connector B		Straight	
Interface, Connector A		NEX10 Male	
Interface, Connector B		N Female	
Specification Sheet Revision Level		А	
Dimensions			
Length		5 m   16.404 ft	
Nominal Size		1/4 in	
Electrical Specifications			
3rd Order IMD		-112 dBm	
3rd Order IMD Test Method		Two +43 dBm carriers	
VSWR/Return Loss			
Frequency Band	VSWR	Return Loss	
(00. 0/0 MI)	1 0 4 5	00.64	

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.065	30.04
1700–2200 MHz	1.083	27.99
2500–2700 MHz	1.106	25.96
3400–3800 MHz	1.222	20.01

## Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

# F1A-XMNF-5M-P



### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

#### Regulatory Compliance/Certifications

#### Agency

ISO 9001:2015

#### Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2