# F1R-NFNR-3M-P

FSJ1RK-50B SureFlex® Jumper with interface types N Female and N Male Right Angle,3 m

#### Product Classification

Product Type		SureFlex® Premium, static PIM
Product Brand		HELIAX®   SureFlex®
Product Series		FSJ1-50B
General Specifications		
Body Style, Connector A		Straight
Body Style, Connector B		Right angle
Interface, Connector A		N Female
Interface, Connector B		N Male
Specification Sheet Revision Level		А
Dimensions		
Length		3 m   9.843 ft
Nominal Size		1/4 in
Electrical Specifications		
3rd Order IMD Static		-107 dBm
3rd Order IMD Static Test Method		Two +43 dBm carriers
VSWR/Return Loss		
Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.152	23.02

Trequency Bana	Volin	Ketain E035 (al
698–960 MHz	1.152	23.02
1700–2200 MHz	1.152	23.02
2200–2700 MHz	1.152	23.02

### Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

# F1R-NFNR-3M-P



### **Environmental Specifications**

EN50575 CPR Cable EuroClass Fire Performance	B2ca
EN50575 CPR Cable EuroClass Smoke Rating	s1a
EN50575 CPR Cable EuroClass Droplets Rating	d0
EN50575 CPR Cable EuroClass Acidity Rating	al
Immersion Test Method	Meets IEC 60529:2001, IP68 in mated condition

ANDREW an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2