F2A-PNMNM-1M5

FSJ2-50 SureFlex® Jumper with interface types N Male and N Male, 1.5

Product Classification

| Product Type | SureFlex® standard |
|------------------------------------|---------------------|
| | |
| Product Brand | HELIAX® SureFlex® |
| Product Series | FSJ2-50 |
| General Specifications | |
| Body Style, Connector A | Straight |
| Body Style, Connector B | Straight |
| Interface, Connector A | N Male |
| Interface, Connector B | N Male |
| Specification Sheet Revision Level | А |
| Dimensions | |
| Length | 1.5 m 4.921 ft |
| Nominal Size | 3/8 in |
| | |

VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|-------|------------------|
| 700–3000 MHz | 1.222 | 20.01 |

Jumper Assembly Sample Label

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 1 of 2

F2A-PNMNM-1M5



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |
| | |



Included Products

| 35422-42 | - | Heat Treated FSJ2-50, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 3/8 in, black PE jacket |
|----------|---|---|
| FSJ2-50 | - | FSJ2-50, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 3/8 in, black PE jacket |



Page 2 of 2