## L4A-NMNF-12M-P

LDF4-50A SureFlex® Jumper with interface types N Male and N Female, 12 m

#### **Product Classification**

**Product Type** SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

Product Series LDF4-50A

General Specifications

Body Style, Connector A Straight

Body Style, Connector B Straight

Interface, Connector A N Male

Interface, Connector B N Female

**Specification Sheet Revision Level** A

**Dimensions** 

**Length** 12 m | 39.37 ft

Nominal Size 1/2 in

**Electrical Specifications** 

**3rd Order IMD Static** -112 dBm

**3rd Order IMD Static Test Method** Two +43 dBm carriers

DTF, Connector A -34 dB

DTF, Connector B -34 dB

### VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.101	26.36
1700-2200 MHz	1.101	26.36
2200-2700 MHz	1.135	23.98



# L4A-NMNF-12M-P

### Jumper Assembly Sample Label



### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

### Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system