# F1A-PNMNM-1M

FSJ1-50A SureFlex® Jumper with interface types N Male and N Male, 1



#### **Product Classification**

**Product Type** SureFlex® standard

**Product Brand** HELIAX® | SureFlex®

**Product Series** FSJ1-50A

### General Specifications

**Body Style, Connector A** Straight **Body Style, Connector B** Straight Interface, Connector A N Male N Male Interface, Connector B

**Specification Sheet Revision Level** Α

#### Dimensions

Length 1 m | 3.281 ft

**Nominal Size** 1/4 in

#### VSWR/Return Loss

**Frequency Band VSWR** Return Loss (dB)

700-3000 MHz 1.222 20.01

## Jumper Assembly Sample Label



# F1A-PNMNM-1M



### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

# Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



#### Included Products

35422-33	<ul> <li>Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE Jacket</li> </ul>
35422-75	<ul> <li>Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket</li> </ul>
FSJ1-50A	<ul> <li>FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket</li> </ul>
FSJ1RK-50A	<ul> <li>FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket, B2ca s1a d0 a1 Compliant</li> </ul>

Page 2 of 2

