F1A-PNMNM-5M

FSJ1-50A SureFlex® Jumper with interface types N Male and N Male, 5



Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50A

General Specifications

Body Style, Connector A Straight **Body Style, Connector B** Straight Interface, Connector A N Male N Male Interface, Connector B

Specification Sheet Revision Level Α

Dimensions

Length 5 m | 16.404 ft

Nominal Size 1/4 in

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

700-3000 MHz 1.288 18

Jumper Assembly Sample Label



F1A-PNMNM-5M



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

35422-33	 Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE Jacket
35422-75	 Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket
FSJ1-50A	 FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket
FSJ1RK-50A	 FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket, B2ca s1a d0 a1 Compliant

Page 2 of 2

