F1A-PNMNM-M5

FSJ1-50A SureFlex® Jumper with interface types N Male and N Male,

0.5 m

Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50A

General Specifications

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector AN MaleInterface, Connector BN Male

Specification Sheet Revision Level A

Dimensions

Length 0.5 m | 1.64 ft

Nominal Size 1/4 in

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

700–3000 MHz 1.222 20.01

Jumper Assembly Sample Label



F1A-PNMNM-M5



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency C	Classification
CHINA-ROHS E	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC C	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS C	Compliant



Included Products

35422-33	 Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Co copper, 1/4 in, black PE Jacket 	axial Cable, corrugated
35422-75	 Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cabl in, black non-halogenated, fire retardant polyolefin jacket 	e, corrugated copper, 1/4
FSJ1-50A	 FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, coblack PE jacket 	orrugated copper, 1/4 in,
FSJ1RK-50A	 FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated cophalogenated, fire retardant polyolefin jacket, B2ca s1a d0 a1 Compliar 	•

Page 2 of 2

