# F2A-HRDM-M51-TMB

### FSJ2-50 SureFlex® Jumper with interface types 4.3-10 Male Right angle 7-16 DIN Male , 0.51m

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

### Product Classification

Product Type		Wireless transmission cable assembly
Product Brand		HELIAX®   SureFlex®
Product Series		FSJ2-50
General Specifications		
Body Style, Connector A		Right angle
Body Style, Connector B		Straight
Interface, Connector A		4.3-10 Male
Interface, Connector B		7-16 DIN Male
Specification Sheet Revision Level		A
Dimensions		
Length		0.51 m   1.673 ft
Nominal Size		3/8 in
Electrical Specifications		
3rd Order IMD		-117 dBm
3rd Order IMD Test Method		Two +43 dBm carriers
VSWR/Return Loss		
Frequency Band	VSWR	Return Loss (dB)

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.101	26.36
1700–2200 MHz	1.101	26.36
2200–2700 MHz	1.101	26.36

## Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

## F2A-HRDM-M51-TMB



## **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

## Included Products

FSJ2-50

FSJ2-50, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 3/8 in, black PE jacket



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2