F4RNA-PNMDM-7M

HELIAX® 1/2" Superflexible Fire retardant SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 7 m

Product Classification

Product Type	Wireless transmission cable assembly
Product Brand	HELIAX® SureFlex®
Product Series	RSJ4-50
General Specifications	
Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	N Male
Interface, Connector B	7-16 DIN Male
Specification Sheet Revision Level	A
Dimensions	
Dimensions Length	7 m 22.966 ft
	7 m 22.966 ft 1/2 in
Length	
Length Nominal Size	
Length Nominal Size Electrical Specifications	1/2 in

Jumper Assembly Sample Label

ANDREW an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 1 of 2

F4RNA-PNMDM-7M



Environmental Specifications

EN50575 CPR Cable EuroClass Smoke Ratings1aEN50575 CPR Cable EuroClass Droplets Ratingd1EN50575 CPR Cable EuroClass Acidity Ratinga1	EN50575 CPR Cable EuroClass Fire Performance	B2ca
	EN50575 CPR Cable EuroClass Smoke Rating	s1a
EN50575 CPR Cable EuroClass Acidity Rating a1	EN50575 CPR Cable EuroClass Droplets Rating	d1
	EN50575 CPR Cable EuroClass Acidity Rating	a1
Immersion Test MethodMeets IEC 60529:2001, IP68 in mated condition	Immersion Test Method	Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Classification

Agency

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

