


C400-TMTM-30-X



Product Classification

| | |
|----------------|------------------------|
| Product Type | Braided cable assembly |
| Product Brand | CNT® |
| Product Series | CNT-400 |

General Specifications

| | |
|------------------------------------|------------------|
| Attachment, Connector A | Field attachment |
| Attachment, Connector B | Field attachment |
| Body Style, Connector A | Straight |
| Body Style, Connector B | Straight |
| Cable Family | CNT-400 |
| Interface, Connector A | TNC Male |
| Interface, Connector B | TNC Male |
| Specification Sheet Revision Level | A |

Dimensions

| | |
|--------------|--------------------|
| Length | 9.14 m 29.987 ft |
| Nominal Size | 0.400 in |

Electrical Specifications

| | |
|------------------|--------|
| DTF, Connector A | -28 dB |
| DTF, Connector B | -28 dB |

Jumper Assembly Sample Label

C400-TMTM-30-X



Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |

Included Products

| | |
|--------------|---|
| 400BPTM-C | - TNC Male for CNT-400 braided cable |
| 400BPTM-C-CR | - TNC Male for CNT-400 braided cable |
| 400PTM-C | - TNC Male for CNT-400 braided cable |
| CNT-400-FR | - CNT-400-FR, CNT® 50 Ohm Braided Coaxial Cable, black non-halogenated, fire retardant polyolefin jacket, Dca s2 d2 Compliant |