F4A-PDRDM-25-X

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male Right Angle and 7-16 DIN Male, 25 ft

Product Classification

Product Type	SureFlex® standard	
Product Brand	HELIAX® SureFlex®	
Product Series	FSJ4-50B	
General Specifications		
Attachment, Connector B	Field attachment	
Body Style, Connector A	Right angle	
Body Style, Connector B	Straight	
Interface, Connector A	7-16 DIN Male	
Interface, Connector B	7-16 DIN Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	7.62 m 25 ft	
Nominal Size	1/2 in	
Electrical Specifications		
DTF, Connector A	-32 dB	
VSWR/Return Loss		
Frequency Band	VSWR, typical	Return Loss, typical (dB)
0.0000 1411	1 100	

0–3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-PDRDM-25-X



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

Included Products

- F4HM-D 4.3-10 Male for 1/2 in FSJ4-50B cable F4HMP-D – 4.3-10 Male Push Pull for 1/2 in FSJ4-50B
- F4HMP-D 4.3-10 Male Push Pull for 1/2 in FSJ4-50E cable
- F4PDMV2-C 7-16 DIN Male for 1/2 in FSJ4-50B cable

