F4A-HPHMHM-8M-X

HELIAX® 1/2" SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male, 8 m

Product Classification

Product Type	SureFlex® HP, HELIAX® performance	
Product Brand	HELIAX® SureFlex®	
Product Series	RSJ4-50	
General Specifications		
Attachment, Connector B	Field attachment	
Body Style, Connector A	Straight	
Body Style, Connector B	Straight	
Interface, Connector A	4.3-10 Male	
Interface, Connector B	4.3-10 Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	8 m 26.247 ft	
Nominal Size	1/2 in	
Electrical Specifications		
DTF, Connector A	-32 dB	
DTF, Connector B	-34 dB	

VSWR/Return Loss

Frequency Band	VSWR, typical	Return Loss, typical (dB)
680-960 MHz	1.101	26.36
1700–2200 MHz	1.101	26.36
2200–2700 MHz	1.135	23.98
3400–3800 MHz	1.222	20.01

ANDREW an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 1 of 2

F4A-HPHMHM-8M-X

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2