F4A-NFNR-5M-P

HELIAX® 1/2" SureFlex® Jumper with interface types N Female and N
Male Right Angle, 5 m

Product Classification

Product Type		SureFlex® Premium, static PIM	
Product Brand		HELIAX® SureFlex®	
Product Series		RSJ4-50	
General Specifications			
Body Style, Connector A		Straight	
Body Style, Connector B		Right angle	
Interface, Connector A		N Female	
Interface, Connector B		N Male	
Specification Sheet Revision Level		В	
Dimensions			
Length		5 m 16.404 ft	
Nominal Size		1/2 in	
Electrical Specifications			
3rd Order IMD Static		-112 dBm	
3rd Order IMD Static Test Method		Two +43 dBm carriers	
DTF, Connector A		-34 dB	
DTF, Connector B		-32 dB	
VSWR/Return Loss			
Frequency Band	VSWR	Return Loss	

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.101	26.36
1700–2200 MHz	1.101	26.36
2200–2700 MHz	1.135	23.98

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-NFNR-5M-P

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ANDREW an Amphenol company

Page 2 of 2

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025