# F4A-PDMDM-8M

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-

#### **Product Classification**

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

**Product Series** FSJ4-50B

General Specifications

Body Style, Connector AStraightBody Style, Connector BStraight

Interface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

**Specification Sheet Revision Level** A

**Dimensions** 

**Length** 8 m | 26.247 ft

Nominal Size 1/2 in

**Electrical Specifications** 

DTF, Connector A -32 dB

DTF, Connector B -32 dB

#### VSWR/Return Loss

Frequency Band VSWR, typical Return Loss, typical (dB)

**0–3000 MHz** 1.106 25.96 **2.2–2.7 GHz** 1.083 27.99

Jumper Assembly Sample Label





## **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant