L4P43A-PDMDM-10M

LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-

Product Classification

Product Type Wireless transmission cable assembly

Product Brand HELIAX® | SureFlex®

Product Series LDF4-50A

General Specifications

Body Style, Connector AStraightBody Style, Connector BStraight

Interface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

Specification Sheet Revision Level A

Dimensions

Length 10 m | 32.808 ft

Nominal Size 1/2 in

Electrical Specifications

DTF, Connector A -32 dB

DTF, Connector B -32 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
800-970 MHz	1.15	23.13
1420-1530 MHz	1.15	23.13
1700-2180 MHz	1.15	23.13

Jumper Assembly Sample Label



L4P43A-PDMDM-10M



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

Included Products

LDF4-50A

LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)

