F1A-PNMNM-1F5

FSJ1-50A SureFlex® Jumper with interface types N Male and N Male,

Product Classification

Product Type	SureFlex® standard
Product Brand	HELIAX® SureFlex®
Product Series	FSJ1-50A
General Specifications	
Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	N Male
Interface, Connector B	N Male
Specification Sheet Revision Level	А
Dimensions	
Length	0.46 m 1.509 ft
Nominal Size	1/4 in
VSWR/Return Loss	

Frequency Band	VSWR	Return Loss (dB)
700–3000 MHz	1.222	20.01

Jumper Assembly Sample Label

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 1 of 2

F1A-PNMNM-1F5



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

35422-33	 Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corr copper, 1/4 in, black PE Jacket 	rugated
35422-75	 Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated co in, black non-halogenated, fire retardant polyolefin jacket 	opper, 1/4
FSJ1-50A	 FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated coppe black PE jacket 	r, 1/4 in,
FSJ1RK-50A	 FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, blac halogenated, fire retardant polyolefin jacket, B2ca s1a dO a1 Compliant 	:k non-

Page 2 of 2

