## F1A-PNMNM-20M

FSJ1-50A SureFlex® Jumper with interface types N Male and N Male,

### **Product Classification**

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

**Product Series** FSJ1-50A

### General Specifications

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector AN MaleInterface, Connector BN Male

Specification Sheet Revision Level A

#### Dimensions

**Length** 20 m | 65.617 ft

Nominal Size 1/4 in

#### VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

**700–3000 MHz** 1.44 15

Jumper Assembly Sample Label



# F1A-PNMNM-20M



## **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

#### Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



#### Included Products

35422-33	<ul> <li>Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density copper, 1/4 in, black PE Jacket</li> </ul>	r Foam Coaxial Cable, corrugated
35422-75	<ul> <li>Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Co in, black non-halogenated, fire retardant polyolefin jacket</li> </ul>	paxial Cable, corrugated copper, 1/4
FSJ1-50A	<ul> <li>FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxia black PE jacket</li> </ul>	al Cable, corrugated copper, 1/4 in,
FSJ1RK-50A	<ul> <li>FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, correlation halogenated, fire retardant polyolefin jacket, B2ca s1a d0 a1</li> </ul>	

Page 2 of 2

