F2A-HMHM-6-P-SGW



FSJ2-50 SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male with HELIAX® SureGuard weatherproofing boot 6 ft

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type		Wireless transmission cable assembly
Product Brand		HELIAX® SureFlex®
Product Series		FSJ2-50
General Specifications		
Body Style, Connector A		Straight
Body Style, Connector B		Straight
Interface, Connector A		4.3-10 Male
Interface, Connector B		4.3-10 Male
Specification Sheet Revision Level		А
Dimensions		
Length		1.829 m 6.001 ft
Nominal Size		3/8 in
Electrical Specifications		
3rd Order IMD Static		-110 dBm
3rd Order IMD Static Test Method		Two +43 dBm carriers
VSWR/Return Loss		
Frequency Band	VSWR	Return Loss (dB)

ANDREW an Amphenol company

Page 1 of 2

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F2A-HMHM-6-P-SGW

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method	Meets IEC 60529:2001, IP68 in mated condition
Weatherproofing Method	HELIAX® SureGuard weatherproofing boot
Dadkaging and Maights	

Packaging and Weights

Included

Weatherproofing boot

ANDREW an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2