# F4A-DMDR-5M-P-SGW



HELIAX® 1/2" SuperflexibleSureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle with HELIAX® SureGuard weatherproofing, 5 m

• If there are threads along the entire device port length, the HELIAX® SureGuard weatherproofing solutions will only seal properly if the HSG-M29-ADPT adapter is installed on the device port

#### **Product Classification**

**Product Type** SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

**Product Series** RSJ4-50

### General Specifications

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

**Specification Sheet Revision Level** B

#### **Dimensions**

**Length** 5 m | 16.404 ft

Nominal Size 1/2 in

### **Electrical Specifications**

**3rd Order IMD Static** -116 dBm

**3rd Order IMD Static Test Method** Two +43 dBm carriers

DTF, Connector A -34 dB

DTF, Connector B -32 dB

### VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
2.2-2.7 GHz	1.135	23.98
698-960 MHz	1.083	27.99
1700-2200 MHz	1.083	27.99

ANDREW®

Page 1 of 2

# F4A-DMDR-5M-P-SGW

3400-3800 MHz

1.222

20.01

### Jumper Assembly Sample Label



### **Environmental Specifications**

**Immersion Test Method**Meets IEC 60529:2001, IP68 in mated condition

Weatherproofing Method HELIAX® SureGuard weatherproofing boot

Packaging and Weights

**Included** Weatherproofing boot

## Regulatory Compliance/Certifications

## Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant

UK-ROHS Compliant/Exempted



