F1A-PNMNF-2

FSJ1-50A SureFlex® Jumper with interface types N Male and N Female,

Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50A

General Specifications

Body Style, Connector A Straight

Body Style, Connector B Straight

Interface, Connector A N Male

Interface, Connector B N Female

Specification Sheet Revision Level A

Dimensions

Length 0.61 m | 2.001 ft

Nominal Size 1/4 in

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

700–3000 MHz 1.288 18

Jumper Assembly Sample Label





Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

| Agency | / | С | l | as | 3 | si | fi | ic | a | ti | 0 | n |
|--------|---|---|---|----|---|----|----|----|---|----|---|---|
| | | | | | | | | | | | | |

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

Included Products

| 35422-33 | - | Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE Jacket |
|------------|---|--|
| 35422-75 | - | Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket |
| FSJ1-50A | - | FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket |
| FSJ1RK-50A | - | FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket, B2ca s1a d0 a1 Compliant |