F4A-HPHMHR-6M



HELIAX® 1/2" SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male Right angle, 6m

WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type SureFlex® HP, HELIAX® performance

Product Brand HELIAX® | SureFlex®

Product Series RSJ4-50

General Specifications

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A4.3-10 MaleInterface, Connector B4.3-10 Male

Specification Sheet Revision Level A

Dimensions

Length 6 m | 19.685 ft

Nominal Size 1/2 in

Electrical Specifications

3rd Order IMD Static Test Method Two +43 dBm carriers

3rd Order IMD, typical-119 dBmDTF, Connector A-34 dBDTF, Connector B-32 dB

VSWR/Return Loss

Frequency Band	VSWR, typical	Return Loss, typical (dB)
3.41-4.0 GHz	1.222	20.01
698-960 MHz	1.083	27.99
1700-2200 MHz	1.083	27.99
2200-2700 MHz	1.135	23.98



F4A-HPHMHR-6M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system