F4A-HPNRNR-1M

HELIAX® 1/2" SureFlex® Jumper with interface types N Male Right Angle and N Male Right Angle, 1 m

Product Classification

Product Type	SureFlex® HP, HELIAX® performance	
Product Brand	HELIAX® SureFlex®	
Product Series	RSJ4-50	
General Specifications		
Body Style, Connector A	Right angle	
Body Style, Connector B	Right angle	
Interface, Connector A	N Male	
Interface, Connector B	N Male	
Orientation	0°	
Specification Sheet Revision Level	А	
Dimensions		
Length	1 m 3.281 ft	
Nominal Size	1/2 in	
Electrical Specifications		
3rd Order IMD Static Test Method	Two +43 dBm carriers	
3rd Order IMD, typical	-112 dBm	
DTF, Connector A	-32 dB	
DTF, Connector B	-32 dB	
VSWR/Return Loss		

Frequency Band	VSWR, typical	Return Loss, typical (dB)
698–960 MHz	1.083	27.99
1700–2200 MHz	1.083	27.99
2200–2700 MHz	1.135	23.98

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-HPNRNR-1M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2