# F4A-PDMDF-2M5

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Female, 2.5 m

### Product Classification

Product Type	SureFlex® standard	SureFlex® standard	
Product Brand	HELIAX®   SureFlex®		
Product Series	FSJ4-50B		
General Specifications			
Body Style, Connector A	Straight		
Body Style, Connector B	Straight		
Interface, Connector A	7-16 DIN Male		
Interface, Connector B	7-16 DIN Female		
Specification Sheet Revision Level	А		
Dimensions			
Length	2.5 m   8.202 ft		
Nominal Size	1/2 in		
Electrical Specifications			
DTF, Connector A	-32 dB		
DTF, Connector B	-32 dB		
VSWR/Return Loss			
Frequency Pond	VSWP typical	Deturn Lee	

Frequency Band	VSWR, typical	Return Loss, typical (dB)
0–3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

## Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

# F4A-PDMDF-2M5



### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

#### Regulatory Compliance/Certifications

#### Agency

ISO 9001:2015

#### Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2