L4A-HPDMDR-9M

LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle, 9 m

Product Classification

2200-2700 MHz

Product Type	SureFlex® HP, HELIAX® performance		
Product Brand		HELIAX® SureFlex®	
Product Series		LDF4-50A	
General Specifications			
Body Style, Connector A		Straight	
Body Style, Connector B		Right angle	
Interface, Connector A		7-16 DIN Male	
Interface, Connector B		7-16 DIN Male	
Specification Sheet Revision Level		А	
Dimensions			
Length		9 m 29.528 ft	
Nominal Size		1/2 in	
Electrical Specifications			
3rd Order IMD Static Test Method		Two +43 dBm carriers	
3rd Order IMD, typical		-116 dBm	
DTF, Connector A		-34 dB	
DTF, Connector B		-34 dB	
VSWR/Return Loss			
Frequency Band	VSWR, t	ypical	Return Loss, typical (dB)
680–960 MHz	1.101		26.36
1700–2200 MHz	1.101		26.36

1.173

21.98

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

L4A-HPDMDR-9M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2