# F4RNA-PNRNM-2M-X

HELIAX® 1/2" Superflexible Fire retardant SureFlex® Jumper with interface types N Male Right Angle and N Male, 2 m

27.99

### Product Classification

P

Product Type		Wireless transmission cable assembly
Product Brand		HELIAX®   SureFlex®
Product Series		FSJ4-50B
General Specifications		
Attachment, Connector B		Field attachment
Body Style, Connector A		Right angle
Body Style, Connector B		Straight
Interface, Connector A		N Male
Interface, Connector B		N Male
Specification Sheet Revision Level		А
Dimensions		
Length		2 m   6.562 ft
Nominal Size		1/2 in
Electrical Specifications		
DTF, Connector A		-32 dB
VSWR/Return Loss		
Frequency Band	VSWR, typical	Return Loss, typical (dB)
0–3000 MHz	1.106	25.96

## Jumper Assembly Sample Label

1.083

2.2-2.7 GHz

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

# F4RNA-PNRNM-2M-X



### **Environmental Specifications**

EN50575 CPR Cable EuroClass Fire Performance	B2ca
EN50575 CPR Cable EuroClass Smoke Rating	s1a
EN50575 CPR Cable EuroClass Droplets Rating	d1
EN50575 CPR Cable EuroClass Acidity Rating	al
Immersion Test Method	Meets IEC 60529:2001, IP68 in mated condition

#### Regulatory Compliance/Certifications

#### Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

#### Included Products

Agency

F4PNMV2-HC - Type N Male for 1/2 in FSJ4-50B cable

Page 2 of 2