F4A-PNMDM-4M5

HELIAX® 1/2" SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 4.5 m

Product Classification

Frequency Band	VSWR, typical	Return Lo	
VSWR/Return Loss			
DTF, Connector B	-32 dB		
DTF, Connector A	-32 dB		
Electrical Specifications			
Nominal Size	1/2 in		
Length	4.5 m 14.764 ft		
Dimensions			
Specification Sheet Revision Level	А		
Interface, Connector B	7-16 DIN Male	7-16 DIN Male	
Interface, Connector A	N Male	N Male	
Body Style, Connector B	Straight		
Body Style, Connector A	Straight		
General Specifications			
Product Series	RSJ4-50		
Product Brand	HELIAX® SureFlex	HELIAX® SureFlex®	
Product Type	SureFlex® standard	SureFlex® standard	

Frequency Band	VSWR, typical	Return Loss, typical (dB)
0–3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-PNMDM-4M5



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2