## L4A-HPDMDM-6M-SGW



LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male with HELIAX® SureGuard weatherproofing, 6 m

• If there are threads along the entire device port length, the HELIAX® SureGuard weatherproofing solutions will only seal properly if the HSG-M29-ADPT adapter is installed on the device port

#### **Product Classification**

**Product Type** SureFlex® HP, HELIAX® performance

Product Brand HELIAX® | SureFlex®

**Product Series** LDF4-50A

Ordering Note ANDREW® standard product in the United States and Canada

### General Specifications

Body Style, Connector AStraightBody Style, Connector BStraight

Interface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

Specification Sheet Revision Level A

#### Dimensions

**Length** 6 m | 19.685 ft

Nominal Size 1/2 in

### **Electrical Specifications**

**3rd Order IMD Static Test Method** Two +43 dBm carriers

 3rd Order IMD, typical
 -116 dBm

 DTF, Connector A
 -34 dB

 DTF, Connector B
 -34 dB

### VSWR/Return Loss

Frequency Band VSWR, typical Return Loss, typical (dB)

**680–960 MHz** 1.065 30.04

ANDREW®
an Amphenol company

## L4A-HPDMDM-6M-SGW

**1700–2200 MHz** 1.065 30.04 **2200–2700 MHz** 1.106 25.96

### Jumper Assembly Sample Label



### **Environmental Specifications**

**Immersion Test Method**Meets IEC 60529:2001, IP68 in mated condition

Weatherproofing Method HELIAX® SureGuard weatherproofing boot

Packaging and Weights

**Included** Weatherproofing boot

### Regulatory Compliance/Certifications

Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted





# L4A-HPDMDM-6M-SGW

### Included Products

HSG-LDF4 – HELIAX® SureGuard® Boot for 1/2 in jumpers to antennas or devices

LDF4-50A - LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)

