1-port omni exposed dipole antenna, 138–150 MHz, 360° HPBW, fixed electrical tilt

- Broad response
- Two-piece mast for ease of shipping

General Specifications

Antenna TypeOmniBandSingle bandColorSilverGrounding TypeRF connector inner conductor and body grounded to reflector and modelPerformance NoteOutdoor usageRadiator MaterialAluminumRF Connector InterfaceN Male	
ColorSilverGrounding TypeRF connector inner conductor and body grounded to reflector and modelPerformance NoteOutdoor usageRadiator MaterialAluminumRF Connector InterfaceN Male	
Grounding TypeRF connector inner conductor and body grounded to reflector and modelPerformance NoteOutdoor usageRadiator MaterialAluminumRF Connector InterfaceN Male	
Performance NoteOutdoor usageRadiator MaterialAluminumRF Connector InterfaceN Male	
Radiator Material Aluminum RF Connector Interface N Male	ounting bracket
RF Connector Interface N Male	
RF Connector Location Bottom	
RF Connector Quantity, high band 0	
RF Connector Quantity, mid band 0	
RF Connector Quantity, low band 1	
RF Connector Quantity, total 1	
Dimensions	
Length 6858 mm 270 in	
Net Weight, without mounting kit 17.2 kg 37.919 lb	
Electrical Specifications	
Impedance 50 ohm	
Operating Frequency Band 138 – 150 MHz	
Polarization Vertical	

Electrical Specifications

Frequency Band, MHz	138-150
Gain, dBi	8.1
Beamwidth, Horizontal,	360

Page 1 of 3



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

DB224-E

degrees

Beamwidth, Vertical, degrees	16
Beam Tilt, degrees	0
VSWR Return loss, dB	1.5 14.0
Input Power per Port, maximum, watts	500

Mechanical Specifications

Wind Loading @ Velocity, maximum	560.5 N @ 100 mph (126.0 lbf @ 100 mph)
Wind Speed, maximum	130 km/h (81 mph)

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

Included Products

DB365-OS

Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance





©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

Product Classification

Product Type	Pipe mounting kit
General Specifications	
Application	Outdoor
Color	Silver
Dimensions	
Compatible Diameter, maximum 88.9 mm 3.5 in	
Compatible Diameter, minimum	33 mm 1.299 in
Weight, net	3.2 kg 7.055 lb
Material Specifications	

Packaging and Weights

Material Type

Included	Brackets Hardware
Packaging quantity	2
Weight, gross	3.6 kg 7.937 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

Galvanized steel



Page 3 of 3



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025