

RVHHTT-65A-R5



12-port sector antenna, 2x 694-960 (R1), 2x 1695-2690 (Y2), 4x 1695-2180 (B1-B2), 4x 2490-2690 (Y1&Y3) MHz, 65° HPBW, 5x RET. Y2 & Y3 share a common RET

- All Internal RET actuators are connected in “Cascaded SRET” configuration
- Supports re-configurable antenna sharing capability enabling control of the internal RET system using up to two separate RET compatible OEM radios

General Specifications

Antenna Type	Sector
Band	Multiband
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	10
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	2
RF Connector Quantity, total	12

Remote Electrical Tilt (RET) Information


RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	2 female 2 male
Input Voltage	10–30 Vdc
Internal RET	High band (4) Low band (1)
Power Consumption, idle state, maximum	1 W
Power Consumption, normal conditions, maximum	8 W
Protocol	3GPP/AISG 2.0 (Single RET)

RVHHTT-65A-R5

Dimensions

Width	395 mm 15.551 in
Depth	228 mm 8.976 in
Length	1500 mm 59.055 in
Net Weight, without mounting kit	24 kg 52.911 lb

Array Layout



Array	Freq (MHz)	Conns	RET (SRET)	AISG RET UID
R1	694-960	1-2	1	CPxxxxxxxxxxxxxxxxR1
B1	1695-2180	3-4	2	CPxxxxxxxxxxxxxxxxB1
B2	1695-2180	5-6	3	CPxxxxxxxxxxxxxxxxB2
Y1	2490-2690	7-8	4	CPxxxxxxxxxxxxxxxxY1
Y3	2490-2690	11-12		
Y2	1695-2690	9-10	5	CPxxxxxxxxxxxxxxxxY1

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

RVHHTT-65A-R5



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2180 MHz 1695 – 2690 MHz 2490 – 2690 MHz 694 – 960 MHz
Polarization	±45°
Total Input Power, maximum	800 W @ 50 °C

Electrical Specifications

	R1	R1	B1-B2	B1-B2	Y2	Y2	Y2	Y1&Y3
Frequency Band, MHz	694–803	824–960	1695–1880	1920–2180	1695–1880	1920–2180	2490–2690	2490–2690
Gain, dBi	14	14.6	16.7	17.3	16.6	17.9	17.4	17.3
Beamwidth, Horizontal, degrees	66	64	71	66	68	59	61	64
Beamwidth, Vertical, degrees	16.6	14.3	6.9	6.3	7.4	6.7	5.4	4.9
Beam Tilt, degrees	2–17	2–17	2–12	2–12	2–12	2–12	2–12	2–12
USLS (First Lobe), dB	15	17	18	17	16	16	17	16
Front-to-Back Ratio at 180°, dB	40	34	32	34	33	36	29	30
Isolation, Cross Polarization, dB	28	28	28	28	25	25	25	28

RVHHTT-65A-R5

Isolation, Inter-band, dB	28	28	28	28	28	28	28	28
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	300	300	250	250	250	250	200	150

Mechanical Specifications

Effective Projective Area (EPA), frontal	0.27 m ² 2.906 ft ²
Effective Projective Area (EPA), lateral	0.2 m ² 2.153 ft ²
Mechanical Tilt Range	0°–18°
Wind Loading @ Velocity, frontal	289.0 N @ 150 km/h (65.0 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	209.0 N @ 150 km/h (47.0 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	495.0 N @ 150 km/h (111.3 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	297.0 N @ 150 km/h (66.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	505 mm 19.882 in
Depth, packed	386 mm 15.197 in
Length, packed	1643 mm 64.685 in
Weight, gross	39 kg 85.98 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



Included Products

BSAMNT-3	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
----------	---	--

* Footnotes

RVHHTT-65A-R5

Performance Note

Severe environmental conditions may degrade optimum performance



BSAMNT-3



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Weight, net 6.2 kg | 13.669 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 6.4 kg | 14.11 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

BSAMNT-3

