F4RNA-PNM-3M

HELIAX® 1/2" Superflexible Fire retardant SureFlex® Jumper with interface type N Male, 3 m

Product Classification

| Product Type | Wireless transmission cable assembly |
|------------------------------------|--------------------------------------|
| Product Brand | HELIAX® SureFlex® |
| Product Series | RSJ4-50 |
| General Specifications | |
| Body Style, Connector A | Straight |
| Interface, Connector A | N Male |
| Interface, Connector B | Sold separately |
| Specification Sheet Revision Level | А |
| Dimensions | |
| Length | 3 m 9.843 ft |
| Nominal Size | 1/2 in |
| Electrical Specifications | |
| DTF, Connector A | -32 dB |
| | |

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4RNA-PNM-3M



Environmental Specifications

| EN50575 CPR Cable EuroClass Smoke Ratings1aEN50575 CPR Cable EuroClass Droplets Ratingd1EN50575 CPR Cable EuroClass Acidity Ratinga1 | EN50575 CPR Cable EuroClass Fire Performance | B2ca |
|--------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|-----------------------------------------------|
| | EN50575 CPR Cable EuroClass Smoke Rating | s1a |
| EN50575 CPR Cable EuroClass Acidity Rating a1 | EN50575 CPR Cable EuroClass Droplets Rating | d1 |
| | EN50575 CPR Cable EuroClass Acidity Rating | a1 |
| Immersion Test MethodMeets IEC 60529:2001, IP68 in mated condition | Immersion Test Method | Meets IEC 60529:2001, IP68 in mated condition |

Regulatory Compliance/Certifications

Classification

Agency

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

