L4A-HPNMNM-3M

LDF4-50A SureFlex ${ m I}$ Jumper with interface types N Male and N Male,
3m

Product Classification

Product Type	SureFlex® HP, HELIAX® performance			
Product Brand	HELIAX® SureFlex®			
Product Series	LDF4-50A			
General Specifications				
Body Style, Connector A	Straight			
Body Style, Connector B	Straight			
Interface, Connector A	N Male			
Interface, Connector B	N Male			
Specification Sheet Revision Level	A			
Dimensions				
Length	3 m 9.843 ft			
Nominal Size	1/2 in			
Electrical Specifications				
3rd Order IMD Static Test Method	Two +43 dBm carriers			
3rd Order IMD, typical	-112 dBm			
DTF, Connector A	-34 dB			
DTF, Connector B	-34 dB			
VSWR/Return Loss				

Frequency Band	VSWR, typical	Return Loss, typical (dB)
680–960 MHz	1.065	30
1700–2200 MHz	1.065	30
2200–2700 MHz	1.106	26

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

L4A-HPNMNM-3M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2