760240957 | 30" Pole Cab with Round Shaft



Bottom of the Pole, 30in Square 4G/5G capable Concealment Enclosure to house and conceal multiple low to high power radios and any other wireless infrastructure equipment in a cabinet at the base of the pole.

- Intended to house and conceal multiple radios and any other wireless infrastructure equipment in a cabinet at the base of the pole
- Flexible configuration accepts low to high-power single or dual band radios, Integrated AC load center/OVP and Disconnect and integrated AC/DC rectifier options

Available with Pole Top concealment, mmWave 5G mounting, luminaire arms.

Available After Market Kits -- ordered separately:

- 860665491-AMK-001 - Ericsson 4480/4415/8863 Radios & 6304 PSU Mounting Kit

Product Classification

Portfolio CommScope®

Product Type Pole cab
Product Brand Metro Cell

Ordering Note CommScope® standard product with terms

Warranty One year

General Specifications

Color Light Gray (RAL 7035)

Color Options Beige-Grey (RAL 7006) | Black (RAL 9005) | Black Green (RAL 6012) | Brown (RAL 8014) | Faux Concrete

6005) | Metallic Silver | Umbra Grey (RAL 7022)

Compatible Foundation Type Poured Concrete | Pre-Cast Concrete

Cooling Fan Cooling

Power Supply Compatibility 6302 | 6304 | 6308 | ABB CC1600 | DELTA 2.0 | PSU-AC-08

Radio Compatibility, Ericsson 1281 | 220x | 440x | 4415 | 4426 | 4449 | 4478 | 4480 | 4490 | 4890 | 6701 | 8843 | 88

Radio Compatibility, Nokia (2) Airscale dual band radios (160W or 320W and (2) Delta 1kW rectifiers (base) | AHFIA | AHFIB | AHLBBA

Radio Compatibility Samsung AT1K01 | AT1K02 | AT1K0X | Diplexer | RF4402D-D1A | RFV01U-D1A | RFV01U-D2A | RT2201-46A

48A

Radios Included None

Dimensions

Height Note 4 ft tall Equipment Cabinet Base

Page 1 of 2



760240957 | 30" Pole Cab with Round Shaft

Pole Height Options 10.668 m | 35 ft | 12.192 m | 40 ft | 6.096 m | 20 ft | 7.62 m | 25 ft | 9.144

m | 30 ft

 Width
 762 mm | 30 in

 Depth
 762 mm | 30 in

Depth Note Square

Pole Diameter 203.2 mm | 8 in

Electrical Specifications

Input Voltage230-115 VacGenerator ConnectionNo connection

Power/Fiber Input AC load center with OVP and disconnect

Material Specifications

Finish Aluminum Chromate

Finish Concealment Covers Powder coated

Material Type Steel

Environmental Specifications

Thermal Compliance GR-487

* Footnotes

Warranty For more information, please consult our Product Warranty guidelines

Pole Height Options Overall AGL Standard Height

