


4103904/10 | 2229V WHRL RG6 QD BC 1000



RG 6 Type Quad Shield Plenum Video Coaxial Cable, white jacket, 1000 ft (305 m) reel

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio

CommScope®

Product Type

Coaxial video cable

General Specifications

Product Number

2229V

Cable Type

Series 6

Center Conductor Type

Solid

Construction Type

Non-armored

Jacket Color

White

Dimensions

Cable Length

304.8 m | 1000 ft

Diameter Over Center Conductor Tolerance

±0.0004 in

Diameter Over Center Conductor, specific

0.0403 in per 1 strand

Diameter Over Dielectric

4.318 mm | 0.17 in

Diameter Over Inner Shield (Braid)

5.131 mm | 0.202 in

Diameter Over Jacket, nominal

6.604 mm | 0.26 in

Diameter Over Jacket Tolerance

±0.004 in

Diameter Over Outer Shield (Braid)

5.893 mm | 0.232 in

Jacket Thickness

0.406 mm | 0.016 in

Jacket Thickness, minimum spot

0.33 mm | 0.013 in

Center Conductor Gauge

18 AWG

Inner Shield (Braid) Gauge

34 AWG

Outer Shield (Braid) Gauge

34 AWG

Electrical Specifications

4103904/10 | 2229V WHRL RG6 QD BC 1000

Capacitance	50.853 pF/m 15.5 pF/ft
Characteristic Impedance	75 ohm
Characteristic Impedance Tolerance	±3 ohm
Conductor dc Resistance	20.997 ohms/km 6.4 ohms/kft
Dielectric Strength, conductor to shield	2500 Vdc
Jacket Spark Test Voltage	2500 Vac
Nominal Velocity of Propagation (NVP)	84 %
Shield dc Resistance	17.388 ohms/km 5.3 ohms/kft
Structural Return Loss	15 dB @ 1000–3000 MHz 20 dB @ 50–1000 MHz 25 dB @ 5-50MHz
Structural Return Loss Test Method	100% Swept Tested

Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
1.0	0.85	0.26
10.0	2.3	0.7
50.0	4.85	1.48
100.0	6.59	2.01
200.0	9.38	2.86
400.0	13.87	4.23
600.0	17.77	5.42
700.0	19.55	5.96
900.0	22.83	6.96
1000.0	24.44	7.45
1450.0	30.64	9.34
2200.0	37.85	11.54
3000.0	42.87	13.07

Material Specifications

Center Conductor Material	Bare copper
Dielectric Material	Foam FEP
Jacket Material	PVC
Inner Shield (Braid) Coverage	60 %
Inner Shield (Braid) Material	Aluminum
Inner Shield (Tape) Material	Aluminum/Poly, bonded

4103904/10 | 2229V WHRL RG6 QD BC 1000

Outer Shield (Braid) Coverage	40 %
Outer Shield (Braid) Material	Aluminum
Outer Shield (Tape) Material	Aluminum/Poly, non-bonded

Mechanical Specifications

Minimum Bend Radius, loaded, times	20 times
Minimum Bend Radius, unloaded, times	10 times

Environmental Specifications

Operating Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Environmental Space	Plenum
Temperature Rating, UL	75 °C 167 °F
Flame Test Method	CMP
Safety Standard	ETL cETL

Packaging and Weights

Cable weight	44.645 kg/km 30 lb/kft
Packaging Type	Reel

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

