## F4A-HMNM-10M-P

# HELIAX® 1/2" SureFlex® Jumper with interface types 4.3-10 Male and N Male, 10m

WARNING: DO NOT MATE WITH 4.1-9.5 DIN

#### **Product Classification**

**Product Type** SureFlex® Premium, static PIM

Α

Product Brand HELIAX® | SureFlex®

Product Series RSJ4-50

#### General Specifications

Body Style, Connector A Straight

Body Style, Connector B Straight

Interface, Connector A 4.3-10 Male

Interface, Connector B N Male

Dimensions

**Length** 10 m | 32.808 ft

Nominal Size 1/2 in

#### **Electrical Specifications**

**Specification Sheet Revision Level** 

**3rd Order IMD Static** -112 dBm

**3rd Order IMD Static Test Method** Two +43 dBm carriers

DTF, Connector A -34 dB

DTF, Connector B -34 dB

#### VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.101	26.36
1700-2200 MHz	1.101	26.36
2200-2700 MHz	1.135	23.98



## F4A-HMNM-10M-P

### Jumper Assembly Sample Label



#### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition