F1A-HMNF-1M-P

FSJ1-50A SureFlex® Jumper with interface types 4.3-10 Male and N Female, 1M

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type		SureFlex® Premium, static PIM	
Product Brand		HELIAX® SureFlex®	
Product Series		FSJ1-50A	
General Specifications			
Body Style, Connector A		Straight	
Body Style, Connector B		Straight	
Interface, Connector A		4.3-10 Male	
Interface, Connector B		N Female	
Specification Sheet Revision Level		А	
Dimensions			
Length		1 m 3.281 ft	
Nominal Size		1/4 in	
Electrical Specifications			
3rd Order IMD		-107 dBm	
3rd Order IMD Test Method		Two +43 dBm carriers	
VSWR/Return Loss			
Fraguanay Pand	Vewd	Poturn Loss	

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.152	23.02
1700–2200 MHz	1.152	23.02
2200–2700 MHz	1.152	23.02

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F1A-HMNF-1M-P



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2